

BULBTITE RIVETS



Material

- Aluminum/Aluminum

Diameter from 5.2 to 7.5 mm

Length from 17.5 to 34.0 mm

- Ideal for applications where sealing is required
- Stable fixation on materials subject to vibrations.
- High tensile and shear strength
- Full aluminum construction for corrosion resistance



Rivet Diameter /mm	Head Diameter /mm	Head Height /mm	Mandrel Diameter /mm	Mandrel Length /mm	Hole Size /mm	Shear /N	Tensile /N
D1	D2	k	d	p	drill		
0.08/-0.15		max.	max.	min.		min.	min.
5.2	11.3-12.5	2.5	3	28	5.3-5.5	3004	2002
6.4	13.5-14.0	2.9	3.9	30	6.4-6.6	4200	2500
7.5	18.2-19.4	4.1	4.4	27	7.6-7.8	6230	4895

PULL THRU(PT) RIVETS



Material

- Steel/Steel
- Stainless steel/Steel

Color painting is available.

Diameter 3.0 mm

Length 2.1-6.3 mm



- Flush set on both sides of the application.
- No loose mandrel heads remain in the application.
- Consistent clamp force.

Rivet Diameter /mm	Head Diameter /mm	Head Diameter /mm	Mandrel Diameter /mm	Mandrel Length /mm	Hole Size /mm	Shear /N	Tensile /N
D1	DK	k	d	p	Drill		
0.05/-0.15	-0.2/+0.4	±0.2	ref.	min.		min.	min.
3.0	5.0	1.0	2.00	26.00	3.1-3.2	2300	2450