

MULTIGRIP BLIND RIVETS



Material

- Aluminum/Steel
- Aluminum/Stainless Steel
- Steel/Steel
- Stainless Steel/Stainless Steel

Color painting is available.



Diameter from 3.2 to 4.8 mm

Length from 6.0 to 30.0 mm

Head Type



Dome Head



Countersunk Head



Large Flange Head

- A wide of grip range, reducing inventory.
- Strong strength, vibration resistant joint
- Accommodates irregular, oversized, slotted or misaligned holes.
- Good appearance and vision

Rivet Diameter /mm	Dome Head		Countersunk Head	Large Flange		Mandrel Diameter /mm	Mandrel Length /mm	Hole Size /mm
	Head Diameter /mm	Head Length /mm	Head Diameter /mm	Head Diameter /mm	Head Length /mm			
D1 +0.08/-0.15	D2	k	D2	D2	k	d	p	Drill
		max.	max.		max.	max.	min.	
3.2	5.8-6.3	1.0	5.5	8.9-9.5	1.4	1.75	26.00	3.3-3.4
4.0	7.5-8.0	1.3	6.5	11.4-12.0	1.7	2.15	27.00	4.1-4.2
4.8	9.0-9.6	1.5	9.7	15.4-16.0	2.0	2.63	28.00	4.9-5.0

Rivet Diameter /mm		Aluminum/Steel	Aluminum /Stainless Steel	Steel/Steel	Stainless Steel /Stainless Steel
3.2	Shear/N	650	650	1100	1600
	Tensile/N	850	850	1200	1900
4	Shear/N	1100	1100	1500	2700
	Tensile/N	1600	1600	1800	3350
4.8	Shear/N	1470	1470	2500	4230
	Tensile/N	2160	2160	3000	4800